

MN54AC139-X REV 1B0

 Original Creation Date: 06/28/96
 Last Update Date: 03/31/97
 Last Major Revision Date: 06/28/96

1-of-4 Decoder/Demultiplexer

General Description

The AC139 is a high-speed, dual 1-of-4 decoder/demultiplexer. The device has two independent decoders, each accepting two inputs and providing four mutually exclusive active LOW outputs. Each decoder has an active LOW Enable input which can be used as a data input for a 4-output demultiplexer. Each half of the AC139 can be used as a function generator providing all four minterms of two variables.

Industry Part Number

54AC139

Prime Die

Z139

NS Part Numbers

 54AC139DMQB
 54AC139FMQB
 54AC139LMQB

Processing

MIL-STD-883, Method 5004

Quality Conformance Inspection

MIL-STD-883, Method 5005

Subgrp	Description	Temp (°C)
1	Static tests at	+25
2	Static tests at	+125
3	Static tests at	-55
4	Dynamic tests at	+25
5	Dynamic tests at	+125
6	Dynamic tests at	-55
7	Functional tests at	+25
8A	Functional tests at	+125
8B	Functional tests at	-55
9	Switching tests at	+25
10	Switching tests at	+125
11	Switching tests at	-55

Features

- Icc reduced by 50%
- Multifunction capability
- Two completely independent 1-of-4 decoders
- Active LOW mutually exclusive outputs
- Outputs source/sink 24 mA
- Standard Military Drawing (SMD)
- AC139: 5962-87623

(Absolute Maximum Ratings)

(Note 1)

Supply Voltage (Vcc)	-0.5V to + 7.0V
DC Input Diode Current (Iik)	
Vi = -0.5V	-20 mA
Vi = Vcc +0.5V	+20 mA
DC Input Voltage (Vi)	-0.5V to Vcc +0.5V
DC Output Diode Current (Iok)	
Vo = -0.5V	-20 mA
Vo = Vcc +0.5V	+20 mA
DC Output Voltage (Vo)	-0.5V to Vcc +0.5V
DC Output Source or Sink Current (Io)	±50 mA
DC Vcc or Ground Current per Output Pin (Icc or Ignd)	±50 mA
Storage Temperature (Tstg)	-65 C to +150 C
Junction Temperature (Tj)	175 C

Note 1: Absolute maximum ratings are those values beyond which damage to the device may occur. The databook specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. National does not recommend operation of FACT™ circuits outside databook specifications.

Recommended Operating Conditions

Supply Voltage (Vcc)	2.0V to 6.0V
Input Voltage (Vi)	0V to Vcc
Output Voltage (Vo)	0V to Vcc
Operating Temperature (Ta)	-55 C to +125 C
Minimum Input Edge Rate (Delta V/Delta t)	
AC Devices	
Vin from 30% to 70% of Vcc	
Vcc @ 3.0V, 4.5V, 5.5V	125 mV/ns

Electrical Characteristics

DC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)
 DC: VCC=3.0V to 5.5V, Temperature Range: -55 C to 125 C. NOTE: -55C TEMPERATURE, SUBGROUP 3 IS GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IIH	High level input current	VCC=5.5V, VM=5.5V, VINH=5.5V, VINL=0.0V	1, 2	INPUT		0.1	uA	1
			1, 2	INPUT		1.0	uA	2, 3
IIL	Low level input current	VCC=5.5V, VM=0.0V, VINH=5.5V, VINL=0.0V	1, 2	INPUT		-0.1	uA	1
			1, 2	INPUT		-1.0	uA	2, 3
VOL	Low level output voltage	VCC=3.0V, VIL=0.9V, VIH=2.1V, IOL=12.0mA	1, 2	OUTPUT		.36	V	1
			1, 2	OUTPUT		.50	V	2, 3
		VCC=3.0V, VIL=0.9V, VIH=2.1V, IOL=50.0uA	1, 2	OUTPUT		.10	V	1, 2, 3
			1, 2	OUTPUT		.36	V	1
		VCC=4.5V, VIL=1.35V, VIH=3.15V, IOL=24.0mA	1, 2	OUTPUT		.36	V	1
			1, 2	OUTPUT		.50	V	2, 3
		VCC=5.5V, VIL=1.65V, VIH=3.85, IOL=24.0mA	1, 2	OUTPUT		.36	V	1
			1, 2	OUTPUT		.50	V	2, 3
VCC=4.5V, VIL=1.35V, VIH=3.15V, IOL=50.0uA	1, 2	OUTPUT		.10	V	1, 2, 3		
	1, 2	OUTPUT		.10	V	1, 2, 3		
VIOH	Dynamic Output Current LOW	VCC=5.5V, VIL=1.65V, VIH=3.85V, IOL=50.0mA	1, 2, 5	OUTPUT		1.65	V	1, 2, 3
VOH	High level output voltage	VCC=3.0V, VIH=2.1V, IOH=-50.0uA, VINH=3.0V, VINL=0.0V	1, 2	OUTPUT	2.90		V	1, 2, 3
			1, 2	OUTPUT	2.56		V	1
		VCC=3.0V, VIH=2.1V, IOH=-12.0mA, VINH=3.0V, VINL=0.0V	1, 2	OUTPUT	2.40		V	2, 3
			1, 2	OUTPUT	3.86		V	1
		VCC=4.5V, VIH=3.15V, IOH=-24.0mA, VINH=4.5V, VINL=0.0V	1, 2	OUTPUT	3.70		V	2, 3
			1, 2	OUTPUT	4.40		V	1, 2, 3
		VCC=4.5V, VIH=3.15V, IOH=-50.0uA, VINH=4.5V, VINL=0.0V	1, 2	OUTPUT	4.86		V	1
1, 2	OUTPUT		4.70		V	2, 3		
VCC=5.5V, VIH=3.85V, IOH=-50.0uA, VINH=5.5V, VINL=0.0V	1, 2	OUTPUT	5.40		V	1, 2, 3		
	1, 2	OUTPUT	3.85		V	1, 2, 3		
VIOH	Dynamic Output Current HIGH	VCC=5.5V, VIH=3.85V, IOH=-50.0mA, VINL=0.0V	1, 2, 5	OUTPUT	3.85		V	1, 2, 3
ICCH	Supply Current Outputs HIGH	VCC=5.5V, VINH=5.5V	1, 2	VCC		4	uA	1
			1, 2	VCC		80	uA	2, 3

Electrical Characteristics

DC PARAMETERS (Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)
 DC: VCC=3.0V to 5.5V, Temperature Range: -55 C to 125 C. NOTE: -55C TEMPERATURE, SUBGROUP 3 IS GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
ICCL	Supply Current Outputs LOW	VCC=5.5V, VINL=0.0V	1, 2	VCC		4	uA	1
			1, 2	VCC		80	uA	2, 3

AC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)
 AC: CL=50pF, RL=500 OHMS, TRISE & TFALL=3ns, Temp Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 11 IS GUARANTEED BUT NOT TESTED.

tpLH(1)	Propagation Delay	VCC=4.5V	3, 4, 6	An to On	1.5	9.0	ns	9
			3, 4, 6	An to On	1.5	11.0	ns	10, 11
tpHL(1)	Propagation Delay	VCC=4.5V	3, 4, 6	An to On	1.5	8.0	ns	9
			3, 4, 6	An to On	1.5	10.0	ns	10, 11
tpLH(2)	Propagation Delay	VCC=4.5V	3, 4, 6	$\bar{E}1$ to On	1.5	8.5	ns	9
			3, 4, 6	$\bar{E}1$ to On	1.5	11.0	ns	10, 11
tpHL(2)	Propagation Delay	VCC=4.5V	3, 4, 6	$\bar{E}1$ to On	1.5	8.0	ns	9
			3, 4, 6	$\bar{E}1$ to On	1.5	10.0	ns	10, 11
tpLH(3)	Propagation Delay	VCC=3.0V	3, 4	An to On	1.0	11.5	ns	9
			3, 4	An to On	1.0	14.5	ns	10, 11
tpHL(3)	Propagation Delay	VCC=3.0V	3, 4	An to On	1.0	10.0	ns	9
			3, 4	An to On	1.0	12.5	ns	10, 11
tpLH(4)	Propagation Delay	VCC=3.0V	3, 4	$\bar{E}1$ to On	1.0	12.0	ns	9
			3, 4	$\bar{E}1$ to On	1.0	14.5	ns	10, 11
tpHL(4)	Propagation Delay	VCC=3.0V	3, 4	$\bar{E}1$ to On	1.0	10.0	ns	9
			3, 4	$\bar{E}1$ to On	1.0	12.5	ns	10, 11

(Continued)

- Note 1: SCREEN TESTED 100% ON EACH DEVICE AT +25C & +125C TEMPERATURE, SUBGROUPS 1, 2, 7, & 8.
- Note 2: SAMPLE TESTED (METHOD 5005, TABLE 1) ON EACH MFG. LOT AT +25C & +125C TEMPERATURE, SUBGROUPS A1, 2, 7, & 8.
- Note 3: SCREEN TESTED 100% ON EACH DEVICE AT +25C TEMPERATURE ONLY SUBGROUP A9.
- Note 4: SAMPLE TESTED (METHOD 5005, TABLE 1) ON EACH MFG. LOT AT +25C & +125C TEMPERATURE, SUBGROUPS A9 & 10.
- Note 5: TRANSMISSION LINE DRIVING TEST, GUARDBAND LIMITS SET FOR +25C, 2 MSEC DURATION MAX.
- Note 6: +25C & +125C MIN LIMITS GUARANTEED FOR 5.5V BY GUARDBANDING 4.5V MIN. LIMITS.